

Generator :

LEROY SOMER

230/400 v , 3 Phase , 50 Hz , PF 0.8

MTU four cycle , Water cooled , 1500 rpm diesel engine

Single bearing alternator , Class H insulation

Electronic Governer



Model	Standby		Prime		Engine				Dimention			Dry weight
	KVA	KW	KVA	KW	Type	Cyl	Bore	Stroke	L	W	H	Kg
GenSet X 715 K	715	572	650	520	12V2000G23E	12V	130	150	3.98	1.63	1.95	5041
X 800 K	800	640	700	560	12V2000G63E	12V	130	150	3.98	1.63	1.95	5241
X 910 K	910	728	827	662	16V2000G23E	16V	130	150	4.33	1.77	2.19	6150
X 1000 K	1001	801	910	728	16V2000G63E	16V	130	150	4.33	1.77	2.19	6177
X 1100 K	1100	880	1000	800	18V2000G63E	18V	130	150	4.57	1.77	2.20	7160
X 1650	1650	1320	1500	1200	12V4000G23F	12V	170	210	4.16	1.89	2.16	10820
X 1650 C	1650	1320	1500	1200	12V4000G23E	12V	170	210	4.16	1.89	2.16	10820
X 1850	1830	1464	1664	1332	12V4000G23F	12V	170	210	4.16	1.89	2.16	11405
X 1850 C	1830	1464	1664	1332	12V4000G23E	12V	170	210	4.05	1.89	2.16	11405
X 2000	2000	1600	1818	1455	12V4000G63F	12V	170	210	4.05	1.89	2.16	11405
X 2000 C	2000	1600	1818	1455	12V4000G63E	12V	170	210	4.05	1.89	2.16	11405
X 2200	2200	1760	2000	1600	16V4000G23F	16V	170	210	4.62	1.89	2.16	13280
X 2200 C	2200	1760	2000	1600	16V4000G23E	16V	170	210	4.62	1.89	2.16	13280
X 2500	2500	2000	2273	1819	16V4000G63F	16V	170	210	4.82	1.89	2.16	14235
X 2500 C	2500	2000	2273	1819	16V4000G63E	16V	170	210	4.82	1.89	2.16	14235
X 2800	2800	2240	2545	2036	16V4000G23F	20V	170	210	5.73	2.25	2.45	17290
X 2800 C	2800	2240	2545	2036	20V4000G23E	20V	170	210	5.73	2.25	2.45	17290
X 3100	3100	2480	2818	2255	20V4000G63F	20V	170	210	5.73	2.25	2.45	18365
X 3100 C	3100	2480	2818	2255	20V4000G63E	20V	170	210	5.73	2.25	2.45	18365
X 3300	3300	2640	3000	2400	20V4000G63LF	20V	170	210	5.73	2.25	2.45	18685
X 3300 C	3300	2460	3000	2400	20V4000G63LE	20V	170	210	5.73	2.25	2.45	18685

